




ITEM	QTY -73	P/N	DESCRIPTION
1	1	B67-43001-73	20° COVER PLATE
2	1	B67-43001-73B	20° COVER PLATE
3	A/R	1637-001	SEE NOTE 1.1
4	A/R	1495	SEE NOTE 1.2
5	A/R	LA4009	SEE NOTE 1.3



B67-43001-73 COVER PLATE ASSEMBLY
(MAKE FROM B67-43001-73F)



SECTION A-A D8-1



RELEASED
2010-09-16

NOTES:

- 1) MATERIAL:
 - 1.1) FOAM: ETHYLENE PROPYLENE NEOPRENE SBR CLOSED-CELL, FLAME RETARDANT, 0.50 THICK, PER ASTM D1056 2A2, SERVICE TEMP -40 °F TO +200 °F, COLOUR: BLACK
REF. TULMAR P/N 1637-001
 - 1.2) FABRIC: 100% 420 DENIER NYLON, MIN THREAD COUNT 35X35, POLYURETHANE COATED ONE SIDE, COLOUR: BLACK
REF. TULMAR P/N 1495
 - 1.3) ADHESIVE: URETHANE WITH CATALYST, TWO PART, CLIFTON LA4009
- 2) FINISH: BOND NEOPRENE TO COVER PLATE USING ADHESIVE. COVER WITH DENIER AS SHOWN.
- 3) TOLERANCES: PER TABLE 1 (ZN A3-1) UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: N/A
- 6) IDENTIFICATION: N/A
- 7) WEIGHT: 0.77 lbs REF
- 8) DENIER NYLON TO BE BONDED ALL AROUND INNER SIDES OF PLATE
- 9) DENIER NYLON TO BE BONDED TO PLATE ON OUTER SIDES

TABLE 1 3

TOLERANCES ON FABRIC (PARTS AND ASSEMBLIES)
±1/8: DIMS <2 ±1/4: DIMS 2 TO <10 ±1/2: DIMS 10 TO <20 ±5/8: DIMS 20 TO <40 ±1.5%: DIMS EQUAL TO OR > 40

C	REDRAWN PREMIER AVIATION DRAWING IAW DART QSI 018, QSI 043 AND TULMAR SAFETY SYSTEMS INC.'S MANUFACTURING PROCESS AND TOLERANCES ON FABRIC; 4.38 WAS 4.25. FOR PREVIOUS REVISIONS, REFER TO SHEETS 7 AND 26 OF PREMIER AVIATION DRAWING No. B67-43001. REASON: SEE PAR#09-011.	MB	10.04.27
REV.	DESCRIPTION	BY	DATE
DESIGN	RW	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN			
CHECKED		DRAWING NO.	REV. C
MFG. APPR.		B67-43001-73	SHEET 1 OF 2
APPROVED		TITLE	SCALE
DE APPR.	N/A	20° COVER PLATE	NTS
DATE	10.04.27	COPYRIGHT © 1995 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	

8 7 6 5 4 3 2 1

D

C

B



A

D



C

B

A



B67-43001-73B BENDING DETAIL
(MAKE FROM B67-43001-73F)



B67-43001-73F COVER PLATE FLAT PATTERN

RELEASED
2010-09-16
MP

- NOTES:**
- 1) MATERIAL: 6061-T6 (OR 6061-T62) ALUMINUM SHEET, 0.032 THICK
PER AMS-QQ-A-250/11 OR AMS 4025/4027 OR ASTM B209
REF. DART SPEC. M6061T6S.032
 - 2) FINISH: CHEMICAL CONVERSION COAT PER DART QSI 005 4.1
POWDER COAT GREEN SANDTEX (4.3.5.8) PER DART QSI 005 4.3
 - 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
 - 4) UNITS: INCHES UNLESS OTHERWISE NOTED
 - 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
 - 6) IDENTIFICATION: IDENTIFY WITH DART P/N "B67-43001-73B" USING FINE POINT PERMANENT INK MARKER
 - 7) WEIGHT: 0.47 lbs

DESIGN	RW	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN			
CHECKED		DRAWING NO.	REV. C
MFG. APPR.		B67-43001-73	SHEET 2 OF 2
APPROVED		TITLE	SCALE
DE APPR.	N/A	20° COVER PLATE	NTS
DATE	10.04.27	COPYRIGHT © 1995 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	

8 7 6 5 4 3 2 1